

## CLAIMS

What is claimed is:

1           1.     A method of authenticating a user at an un-trusted computing  
2     system, the user having at least one portable computing device coupled to a  
3     peripheral device, the method comprising:  
4           randomly generating a temporary password by the portable computing  
5     device;  
6           sending the temporary password to the peripheral device;  
7           rendering the temporary password by the peripheral device for perception  
8     by the user;  
9           inputting a password, by the user, into the un-trusted computing system;  
10          receiving, by the portable computing device, the password input by the  
11     user from the un-trusted computing system; and  
12          allowing access to the portable computing device using the un-trusted  
13     computing system when the temporary password matches the user-inputted  
14     password.

1           2.     The method of claim 1, wherein randomly generating the temporary  
2     password comprises randomly generating the temporary password periodically.

1           3.     The method of claim 1, wherein randomly generating the temporary  
2     password comprises randomly generating the temporary password in response  
3     to a user-initiated action to the peripheral device.

1           4.     The method of claim 1, wherein the temporary password is valid for  
2     only a predetermined period of time.

1           5.     The method of claim 4, wherein the predetermined period of time is  
2     less than one minute.

3

1           6. The method of claim 1, wherein sending the temporary password to  
2 the peripheral device comprises sending the temporary password from the  
3 portable computing device to the peripheral device over a secure wireless link.

4

1           7. The method of claim 1, wherein rendering the temporary password  
2 comprises displaying the temporary password on a display of the peripheral  
3 device.

4

1           8. The method of claim 7, further comprising displaying a number of  
2 seconds until the temporary password expires on a display of the peripheral  
3 device.

4

1           9. The method of claim 1, wherein rendering the temporary password  
2 comprises rendering the temporary password audibly for hearing by the user.

3

1           10. The method of claim 1, wherein the password comprises at least one  
2 of numbers, letters, symbols, images, and shapes.

3

1           11. The method of claim 1, further comprising detecting initiation of an  
2 action by the user to the peripheral device to cause the rendering of the  
3 temporary password.

4

1           12. The method of claim 1, further comprising:  
2           generating an indicator by the portable computing device;  
3           sending the indicator to the peripheral device and the un-trusted  
4 computing system;  
5           rendering the indicator by the peripheral device for perception by the user;  
6           rendering the indicator by the un-trusted computing system for perception  
7 by the user;

8 wherein the user inputs a password only when the indicator rendered by  
9 the peripheral device matches the indicator rendered by the un-trusted  
10 computing system the user desires to use.

11  
1 13. The method of claim 1, wherein the peripheral device is at least one  
2 of worn by the user and carried by the user.

3  
1 14. The method of claim 1, wherein the portable computing device and  
2 the un-trusted computing system communicate over a wireless link.

3  
1 15. An article comprising: a storage medium having a plurality of machine  
2 readable instructions, wherein when the instructions are executed by a  
3 processor, the instructions provide for authenticating a user of an un-trusted  
4 computing system, the user having at least one portable computing device  
5 coupled to a peripheral device, by randomly generating a temporary password by  
6 the portable computing device, by sending the temporary password to the  
7 peripheral device, by receiving at the portable computing device a password  
8 input by the user from the un-trusted computing system, and by allowing access  
9 to the portable computing device using the un-trusted computing system when  
10 the temporary password matches the user-inputted password.

11  
1 16. The article of claim 15, wherein instructions for randomly generating  
2 the temporary password comprise instructions for randomly generating the  
3 temporary password periodically.

4  
1 17. The article of claim 15, wherein the temporary password is valid for  
2 only a predetermined period of time.

3  
1 18. The article of claim 17, wherein the predetermined period of time is  
2 less than one minute.

1           19. The article of claim 15, wherein instructions for sending the temporary  
2 password to the peripheral device comprise instructions for sending the  
3 temporary password from the portable computing device to the peripheral device  
4 over a secure wireless link.

1           20. The article of claim 15, wherein the password comprises at least one  
2 of numbers, letters, symbols, images, and shapes.

1           21. A system for authenticating a user desiring to use an un-trusted  
2 computing system comprising:  
3           a portable computing device; and  
4           a peripheral device, coupled to the portable computing device, capable of  
5 rendering a password for perception by the user;  
6           the portable computing device comprising:  
7                 a random password generator to randomly generate a temporary  
8 password;  
9                 a memory to store instructions and data; and  
10                a processor to execute the instructions obtained from the memory  
11 to send the temporary password to the peripheral device for rendering to  
12 the user, to receive from the un-trusted computing system a password  
13 input by the user; and to allow access to the data by the un-trusted  
14 computing system when the temporary password matches the user-  
15 inputted password.

1           22. The system of claim 21, wherein the peripheral device comprises a  
2 display and renders the password by displaying the password on the display.

1           23. The system of claim 21, wherein the portable computing device  
2 communicates with the peripheral device over a secure wireless link.

1           24. The system of claim 21, wherein the portable computing device  
2 communicates with the un-trusted computing system over a wireless link.  
3

1           25. The system of claim 21, wherein the random password generator  
2 randomly generates the temporary password periodically, the temporary  
3 password valid for only a predetermined period of time.  
4

1           26. The system of claim 21, wherein the peripheral device is capable of  
2 being at least one of worn and carried by the user.  
3

1           27. The system of claim 21, wherein the peripheral device comprises an  
2 input mechanism activation of which initiates rendering of the password by the  
3 peripheral device.  
4

1           28. The system of claim 21, wherein the peripheral device comprises an  
2 input mechanism activation of which causes the portable computing device to  
3 randomly generate a new temporary password.